



Cilindros hidráulicos de simple y doble efecto



REF.	Ø (mm)	Ø (pulgadas)	J (CARROSA) (CMOS)	E	E'	Ø	F	G	H	I	J	K	L	M	N (mm)	O	P
8000T	30	3/8	50 - 2000	10 ± 0,2	24	Ø16x0,5	24	24	24	25	75	95	50	40	104	20	11
8001T	32																
8002T	33																
8003T	35	1 1/8	50 - 2000	12 ± 0,2	25	Ø18x0,5	40	32	32	40	94	118	50	50	108	20	12
8004T	36																
8005T	38																
8006T	38	1 1/2	50 - 2000	14 ± 0,2	30	Ø20x0,5	43	35	38	48	105	130	50	60	108	25	15
8007T	40																
8008T	40																
8009T	40																
8010T	40	1 1/2	50 - 2000	16 ± 0,2	30	Ø22x0,5	45	38	38	58	100	130	25	50	108	30	16
8011T	42																
8012T	42																
8013T	42																
8014T	42	1 3/8	50 - 2000	18 ± 0,2	30	Ø22x0,5	45	38	38	58	100	130	25	75	108	30	17
8015T	45																
8016T	45																
8017T	45																
8018T	45	1 3/4	50 - 2000	18 ± 0,2	30	Ø22x0,5	45	38	38	58	100	130	25	95	108	30	18
8019T	50																
8020T	50																
8021T	50																
8022T	50	1 3/4	50 - 2000	18 ± 0,2	70	Ø22x0,5	60	38	38	58	100	130	25	110	100	40	20
8023T	55																
8024T	55																
8025T	55	1 3/4	50 - 2000	18 ± 0,2	80	Ø24x0,5	62	40	40	62	120	150	25	100	100	40	20
8026T	60																
8027T	60	1 3/2	50 - 2000	22 ± 0,2	100	Ø24x0,5	60	50	50	100	150	200	40	100	100	50	20
8028T	63																
8029T	63	1 3/2	50 - 2000	22 ± 0,2	110	Ø26x0,5	100	50	50	130	200	200	60	100	100	50	20
8030T	70																
8031T	70	1 3/2	50 - 2000	24 ± 0,2	140	Ø26x0,5	110	60	60	130	200	220	60	100	100	50	20